



cavagna group

Advanced solutions for gas control

Forklift Equipment



Faster Connection

Lower Fugitive Emissions

More Ergonomic



66.1327
66.0.290.1327

3/4" M NPT Forklift
EN 12806 Filler Valve



Container Connection

3/4" M NPT

Wrench Hex Flat

1-3/4"

Cavagna North America Inc. 50 Napoleon Court, Somerset NJ 08873 Phone 732-469-2100, Fax 732 469 3344
Cavagna West 1393 Dodson Way-A Riverside, CA 92507 Phone 732-469-2100, Fax 732 469 3344
Info@cavagna.com - www.cavagnagroup.com



cavagna group

Advanced solutions for gas control

Forklift Equipment



80.2064

80.0.390.2064

Service Valve

with Double O-ring Stem Seal. Sturdy brass handwheel less likely to break, even with rough handling.

Container Connection

3/4" M.NGT



Outlet Connection

3/8" 18 NPT

66.0248

66.0.290.0248

Internal Pressure Relief Valve

Designed specifically for use on Forklift cylinders.

Container Connection

3/4" NPT



Wrench Hex Flat

1-1/16"

66.1122

66.0.290.1122

Forklift Filler Valve

3/4" M NPT.
Double Soft seal.

Container Connection

3/4" M NPT



Wrench Hex Flat

1-3/4"

66.1023

66.0.290.1023

Forklift Connector

Female coupling ACME.
For installation on the carburetor fuel line.

Inlet A

1-1/4" F.ACME



Outlet B

1/4" F.NPT

66.1024

66.0.290.1024

Forklift Connector

Half coupling ACME.
For installation between the Propane engine fuel line and the Forklift service valve.

Inlet A

3/8" F.NPT



Outlet B

1-1/4" M.ACME

66.1072

66.0.290.1072

Fixed Liquid Level Gauge

Special DT length available. These valves incorporate a No. 54 drill size orifice. Captive screw.

Container Connection

1/4" M NPT



DT Length

12"

4CA15210 - Rev.0 Eng. - 02/15